



A Quality Assurance Management System for Retrofitting with Good Indoor Environment and Energy Efficiency

Åsa Wahlström, Kristina Mjörnell and John Rune Nielsen

SP Technical Research Institute of Sweden



Åsa Wahlström, Ökosan 2007

Background:



A certified
labelling
system



To establish means of control
which will assure good indoor
environment



Åsa Wahlström, Ökosan 2007

The performance of the building – a question of system

Effective energy use ↔ Adequate indoor climate



Åsa Wahlström, Ökosan 2007

Quality assurance of indoor environment

- Moisture assurance
- Indoor climate
- IAQ
- Choice of material
- Radon
- Ventilation
- Air tightness
- Sound
- Lighting
- Tap water temperature
- Cleaning



Specific predefined requirements



Åsa Wahlström, Ökosan 2007

Scope

New construction



Retrofit



Existing buildings



Schools
Kindergartens
Multifamily houses
Offices
Hospitals



Åsa Wahlström, Ökosan 2007

Target determination of energy use : First Energy Analyse




- Energy status (the envelope and services, climate)
- Energy aspects (category, activity)
- Energy performance (before retrofit)
- Present organisation



Åsa Wahlström, Ökosan 2007

Quality assurance system




Åsa Wahlström, Ökosan 2007

- building categories and
- property management organisations



Åsa Wahlström, Ökosan 2007

Quality assurance system



Åsa Wahlström, Ökosan 2007

Routines and means of control for clients, architects, builders, consultants

- Responsible persons are selected for all actions
- Competence and education need is defined for all actions
- Communication and information routines
- Documentation of the routines



Åsa Wahlström, Ökosan 2007

Why retrofit of residential building stock?

- several million residential buildings in the EU
- many were built before the oil crises and has high energy use
- many years of neglected maintenance
 - both the building envelope and building services



Åsa Wahlström, Ökosan 2007

Why retrofit of residential building stock?

- the retrofit provides an opportunity for cost-effective energy measures
- since social housing stocks consist of many similar buildings, the measures can be replicated



Åsa Wahlström, Ökosan 2007

	Participant	Short name	Country
1	SP Technical Research Institute of Sweden	SP	Sweden
2	Trama Tecno Ambiental S.L.	TTA	Spain
3	Helsinki University of Technology	TKK	Finland
4	AEE - Institute for Sustainable Technologies	AEE INTEC	Austria
5	Trecodome	Trecodome	The Netherlands
6	Energy Agency of Plovdiv	EAP	Bulgaria
7	AB Alingsåshem	Alingsåshem	Sweden
8	POMAA S.L.	POMAA	Spain
(9)	VVO		Finland
(10)	GLOWOG		Austria



Åsa Wahlström, Ökosan 2007



Objective

- Exchange knowledge and develop energy improvement measures for retrofitting of social housing
- Adopt and develop QA system for each country with their different conditions
- Demonstrate actions in pilot projects



Åsa Wahlström, Ökosan 2007

Pilot projects

Sweden, Alingsås

Spain, Barcelona

Austria, Graz

Finland, Helsinki



Åsa Wahlström, Ökosan 2007

Sweden Alingsåshem




Åsa Wahlström, Ökosan 2007

- Insulations of walls, balconies, attics and basements
- Thermal bridges (balcony)
- Tight doors
- Passive house windows
- Solar collectors
- District heating (biomass)



Åsa Wahlström, Ökosan 2007



Energianvändning: (kWh/kvm år) 22° inomhustemperatur	Före renovering	Efter renovering
Uppvärmning:	115	27
Varmvatten:	42	25
Hushållsel:	39	27
Fastighetsel (trapphus, tvättstuga etc):	20	13
Summa:	216	92



Åsa Wahlström, Ökosan 2007

3 building types:

Year of construction: 1952/ 1959 /1970

Heating: decentral; 13% solid fuel;
33% Oil; 54% electric

Hot water: decentral electric boilers

Ventilation: natural ventilation



Dieselweg 12, 14



Dieselweg 2-10



Dieselweg 6, 8, 4

Renovation needs:

Insulation: (total heated building envelope)

- Facade (U-value: $< 0,2 \text{ W/m}^2\text{K}$)
- Top floor (U-value: $< 0,2 \text{ W/m}^2\text{K}$)
- Ground floor (U-value: $< 0,2 \text{ W/m}^2\text{K}$)

Windows exchange; Target U_w -value: $< 0,85 \text{ W/m}^2\text{K}$

Balcony renewal / living room extension (thermal bridge)

HVAC-System:

Central radiator heating system; (Target: Biomass district heating)

Solar thermal system for hot water and heating (2-pipe network)

Ventilation system with heat recovery (central or decentral)

QA-system: SPCR 114E Handbook

www.sp.se



Åsa Wahlström, Ökosan 2007